NSN 3020-01-008-5302

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-008-5302

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 2.5000 inches |
| Teeth Quantity: |
| 120 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade c |
| Mounting Hole Type And Quantity: |
| 2 plain axially through body, first end |
| Outside Diameter: |
| 2.542 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.250 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.241 inches both ends |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 0.500 inches first end |
| Precision Classification: |
| Quality number 10 |
| Mounting Hole Diameter: |
| 0.109 inches axially through body, first end |
| Bolt Hole Circle Diameter: |
| 0.438 inches axially through body, first end |
| Special Features: |
| Mtg holes 180 degrees apart |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6, t4 federal specification single material response |

NSN 3020-01-008-5302

Spur Gear - Page 2 of 2



| Style | Desi | ignator: |
|-------|------|----------|
|-------|------|----------|

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300