NSN 3020-01-009-6493

Spur Gear - Page 1 of 2

Body Style: Plain, solid

Clamp

Attachment Method:



View Online at https://aerobasegroup.com/nsn/3020-01-009-6493

| Pitch Diameter: |
|---|
| 1.2500 inches |
| Teeth Quantity: |
| 80 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade d |
| Outside Diameter: |
| 1.280 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.281 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.250 inches both ends |
| Hub Style Designator: |
| Split first end |
| Hub Diameter: |
| 0.312 inches first end |
| Clamping Surface Length: |
| 0.250 inches first end |
| Precision Classification: |
| Quality number 12 |
| Special Features: |
| Hub is also stepped, 0.375 in.Dia, 0.031 in.Lg |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6, t4 federal specification single material response |
| Surface Treatment: |
| Anodize hub |
| Surface Treatment Specification: |
| Mil-a-8625, type 1 military specification single treatment response hub |

NSN 3020-01-009-6493

Spur Gear - Page 2 of 2



| Style Designator: |
|-------------------|
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| • |

Mil-std (military Standard):

Mil-a-8625 spec.