## NSN 3020-01-009-6493

Spur Gear - Page 1 of 2

**Body Style:** Plain, solid

Clamp

**Attachment Method:** 



View Online at https://aerobasegroup.com/nsn/3020-01-009-6493

Pitch Diameter:
1.2500 inches
Teeth Quantity:
80
Bore Style:
Plain both ends
Backlash Designation:
Grade d
Outside Diameter:
1.280 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.281 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.312 inches first end
Clamping Surface Length:
0.250 inches first end
Precision Classification:
Quality number 12
Special Features:
Hub is also stepped, 0.375 in.Dia, 0.031 in.Lg
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize hub
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response hub

## NSN 3020-01-009-6493

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
•

Mil-std (military Standard):

Mil-a-8625 spec.