NSN 3020-01-010-1658

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-010-1658

Attachment Method:
Clamp
Pitch Diameter:
0.9375 inches
Teeth Quantity:
60
Bore Style:
Plain both ends
Outside Diameter:
0.968 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.221 inches first end
Face Width:
0.104 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.185 inches first end
Precision Classification:
Quality number 12
End Diameter:
0.187 inches first end
First Step Length:
0.036 inches first end
First Step Diameter:
0.437 inches first end
Material:
Steel comp 303 hub
Material Specification:
Qq-s-764, cond a federal specification single material response hub
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response body

Protruding hub

Style Designator:

NSN 3020-01-010-1658

Spur Antibacklash Gear - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-a-8625 spec.