## NSN 3020-01-011-6775

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-011-6775

| Body St | vle |
|---------|-----|

Plain, solid

**Attachment Method:** 

Mounting hole

**Pitch Diameter:** 

1.7000 inches

#### **Teeth Quantity:**

34

#### Mounting Hole Type And Quantity:

4 plain axially through flange

#### **Outside Diameter:**

1.8100 inches

#### Tooth Form:

Standard

#### Flange Diameter:

2.340 inches

## Pressure Angle:

20.0000 degrees

## Flange Thickness:

0.070 inches

#### Face Width:

0.250 inches

#### Distance Between Outer Body Face And Inner Flange Face:

0.5650 inches

#### Hub Style Designator:

Plain first end

#### Hub Diameter:

1.500 inches first end

#### **Precision Classification:**

Quality number 10

#### Mounting Hole Diameter:

0.218 inches axially through flange

#### **Bolt Hole Circle Diameter:**

2.000 inches axially through flange

#### **Special Features:**

Stepped hub on gear end, 0.7875 in. Dia, 0.369 in. Lg; 1st step 1.577 in. Dia, 0.131 in. Lg; 2nd step 1.700 in. Diameter 0.099 in. Lg

## Material:

Steel

#### Style Designator:

Flanged end

#### Shelf Life:

N/a

# NSN 3020-01-011-6775

Spur Gear - Page 2 of 2

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A27300

