
NSN 3020-01-011-6776

Spur Gear - Page 1 of 2



AeroBase Group

Body Style: Webbed, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.4166 inches **Teeth Quantity:** 40 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 threaded transversely through hub, first end **Outside Diameter:** 0.4370 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.236 inches first end Face Width: 0.045 inches **Bore Diameter:** 0.0939 inches both ends Hub Style Designator: 1 groove first end **Hub Diameter:** 0.2495 inches first end First Groove Width: 0.0305 inches first end First Groove Diameter: 0.2115 inches first end **Distance From End To First Groove:** 0.0430 inches first end **Special Features:** Contains 2 holes 0.031 in. Dia. Approximatelt 30 degrees apart in gear side

NSN 3020-01-011-6776

Spur Gear - Page 2 of 2



Material:

Steel comp 303

Material Specification:

Mil-s-7720, cond a military specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-std-171, finish no. 5.4.1 military standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization: No Fiig: A27300

Mil-std (military Standard):

Mil-s-7720 spec.