NSN 3020-01-011-6776

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-011-6776

Body Style:
Webbed, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.4166 inches
Teeth Quantity:
40
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
0.4370 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.236 inches first end
Face Width:
0.045 inches
Bore Diameter:
0.0939 inches both ends
Hub Style Designator:
1 groove first end
Hub Diameter:
0.2495 inches first end
First Groove Width:
0.0305 inches first end
First Groove Diameter:
0.2115 inches first end
Distance From End To First Groove:
0.0430 inches first end
Special Features:
Contains 2 holes 0.031 in Dia Approximatelt 30 degrees apart in gear side

NSN 3020-01-011-6776

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-s-7720 spec.



Material:
Steel comp 303
Material Specification:
Mil-s-7720, cond a military specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-std-171, finish no. 5.4.1 military standard single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300