## NSN 3020-01-012-2195



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-012-2195 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.8333 inches **Teeth Quantity:** 80 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 plain transversely through hub, first end **Outside Diameter:** 0.8542 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.1500 inches first end **Face Width:** 0.100 inches **Bore Diameter:** 0.0901 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.3400 inches first end **Precision Classification:** Quality number 10 **Special Features:** Mtg holes 120 degrees apart

Material:

Steel comp 303

## NSN 3020-01-012-2195

Spur Gear - Page 2 of 2



| Material Specification:   |
|---|
| Qq-s-764, cond a federal specification single material response           |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Mil-std-171, finish no. 5.4.1 military standard single treatment response |
| Style Designator:   |
| Protruding hub  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |

Mil-std (military Standard): Mil-std-171 spec.

A27300