## NSN 3020-01-012-2197

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-012-2197

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.4165 inches **Teeth Quantity:** 50 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 plain transversely through hub, first end **Outside Diameter:** 0.4333 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.0050 inches second end Face Width: 0.095 inches **Bore Diameter:** 0.0936 inches both ends Hub Style Designator: Plain second end **Hub Diameter:** 0.2500 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 303 **Material Specification:** Qq-s-764, type 303 federal specification single material response Surface Treatment: Passivate **Surface Treatment Specification:** 

Mil-std-171, finish no. 5.4.1 military standard single treatment response

## NSN 3020-01-012-2197

Spur Gear - Page 2 of 2

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.

