NSN 3020-01-012-2199

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-012-2199 **Attachment Method:** Setscrews Pitch Diameter: 0.5833 inches **Teeth Quantity:** 70 **Bore Style:** Plain both ends **Outside Diameter:** 0.6000 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.184 inches first end **Face Width:** 0.096 inches **Bore Diameter:** 0.090 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.250 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 303 **Material Specification:** Qq-s-764, type 303, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-std-171, finish no. 5.4.1 military specification single treatment response **Style Designator:** Protruding hub Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

NSN 3020-01-012-2199

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.