# NSN 3020-01-012-2199

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-012-2199

## Attachment Method:

Setscrews

**Pitch Diameter:** 

0.5833 inches

# Teeth Quantity:

70

## Bore Style:

Plain both ends

## **Outside Diameter:**

0.6000 inches

#### Tooth Form:

Standard

#### **Pressure Angle:**

20.0000 degrees

#### Distance Between Body Face And Protruding Hub End:

0.184 inches first end

#### Face Width:

0.096 inches

#### Bore Diameter:

0.090 inches both ends

## Hub Style Designator:

Pinned first end

## Hub Diameter:

0.250 inches first end

## **Precision Classification:**

Quality number 10

#### Material:

Steel comp 303

#### **Material Specification:**

Qq-s-764, type 303, cond a federal specification single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Mil-std-171, finish no. 5.4.1 military specification single treatment response

#### Style Designator:

Protruding hub

### Shelf Life:

N/a

### Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

# NSN 3020-01-012-2199

Spur Antibacklash Gear - Page 2 of 2

Fiig: A27300 Mil-std (military Standard):

Mil-std-171 spec.

