NSN 3020-01-012-9588



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-012-9588 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.5310 inches **Teeth Quantity:** 98 **Mounting Hole Thread Series Designator:** Unc axially through body, first end **Mounting Hole Thread Size:** 0.112 inches axially through body, first end **Mounting Hole Type And Quantity:** 1 plain axially through body, first end and 3 threaded axially through body, first end **Outside Diameter:** 1.562 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.812 inches first end **Face Width:** 0.125 inches **Hub Style Designator:** 1 step first end **End Length:** 0.734 inches first end **Precision Classification:** Quality number 10 **End Diameter:** 0.250 inches first end First Step Length: 0.047 inches first end First Step Diameter: 0.875 inches first end

Mounting Hole Diameter: 0.098 inches axially through body, first end **Bolt Hole Circle Diameter:** 0.625 inches axially through body, first end Material: Stainless steel

NSN 3020-01-012-9588

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-f-14072 spec.



Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300