## NSN 3020-01-013-0010



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-013-0010 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.1875 inches **Teeth Quantity:** 18 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.208 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.0312 inches second end **Face Width:** 0.095 inches **Bore Diameter:** 0.094 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 0.135 inches second end **End Length:** 

0.156 inches first end

0.250 inches first endFirst Step Length:0.050 inches first endFirst Step Diameter:0.145 inches first end

**End Diameter:** 

## NSN 3020-01-013-0010

Spur Gear - Page 2 of 2

Mil-std-171 spec.



Special Features:
Mtg holes spaced 120 degrees apart
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-std-171, finish no. 5.4.1 military standard single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):