NSN 3020-01-016-9958

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-016-9958

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.8750 inches **Teeth Quantity:** 42 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end Mounting Hole Thread Size: 0.138 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 0.914 inches Nominallength: 0.335 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.210 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.250 inches both ends Hub Style Designator: Pinned first end **Hub Diameter:** 0.437 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material: Aluminum alloy 2024 **Material Specification:**

Qq-a-225/6, t4 federal specification single material response

NSN 3020-01-016-9958

Spur Gear - Page 2 of 2



Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.