## NSN 3020-01-019-1717



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-019-1717 **Body Style:** Plain, solid **Attachment Method:** Press fit Pitch Diameter: 5.6000 inches **Teeth Quantity:** 84 **Bore Style:** Plain both ends **Backlash Designation:** Grade a **Hardness Rating:** 40.0 rockwell c and 45.0 rockwell c **Outside Diameter:** 5.707 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees Face Width: 0.125 inches **Bore Diameter:** 4.990 inches both ends **Precision Classification:** Quality number 8 Material: Steel comp 4140 or steel comp 8640 **Material Specification:** Astm a322 assn standard 1st material response or astm a331 assn standard 2nd material response **Surface Treatment:** Phosphate zinc **Surface Treatment Specification:** Mil-std-171 fn5.3.2.2 military standard single treatment response **Style Designator:** Hubless Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 3020-01-019-1717

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.