NSN 3020-01-021-8878

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-021-8878

| Counterbore Depth: |
|---|
| 0.187 inches |
| Outside Diameter: |
| 1.122 inches |
| Overall Length: |
| 0.450 inches |
| Bore Diameter: |
| 0.140 inches |
| Bore Length: |
| 0.450 inches |
| Pitch Diameter: |
| 1.082 inches |
| Face Width: |
| 0.340 inches |
| Design Form: |
| Spoked |
| Bore Type: |
| Straight |
| Counterbore Location: |
| Aa end |
| Keying Facility: |
| Not included |
| Lightening Hole: |
| Not included |
| Protruding Hub Characteristic: |
| Stepped |
| Groove/step Location: |
| Both ends |
| Teeth Row Quantity: |
| 1 |
| Teeth Quantity Per Row: |
| 12 |
| Hardness Rating Test Method: |
| Not rated |
| Bore Bearing: |
| Not included |
| Hub End Outside Diameter And Location: |
| 0.498 inches both ends |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.060 inches aa end and 0.050 inches bb end |

First Step Length And Location:

0.060 inches aa end and 0.050 inches bb end

NSN 3020-01-021-8878

Sprocket Wheel - Page 2 of 2

No Fiig: T353-c



Second Step Length And Location: 0.110 inches aa end and 0.170 inches bb end **Hub End Outside Diameter And Location:** 0.498 inches both ends **Special Features:** First end has hexagon shaped counterbore, 0.312 in. Across flats Material: Nylon and fibreglass Material: Nylon and fibreglass **Style Designator:** Webbed or spoked **Surface Treatment:** Any acceptable Shelf Life: N/a **Unit Of Measure: Demilitarization:**