Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-021-8878

## Counterbore Depth:

0.187 inches

**Outside Diameter:** 

1.122 inches

### **Overall Length:**

0.450 inches

#### Bore Diameter:

0.140 inches

#### Bore Length:

0.450 inches

#### Pitch Diameter:

1.082 inches

#### Face Width:

0.340 inches

#### **Design Form:**

Spoked

# Bore Type:

\_\_\_\_\_

# Straight

**Counterbore Location:** 

Aa end

#### Keying Facility:

Not included

#### Lightening Hole:

Not included

#### **Protruding Hub Characteristic:**

Stepped

#### Groove/step Location:

Both ends

#### Teeth Row Quantity:

1

# Teeth Quantity Per Row:

12

# Hardness Rating Test Method:

Not rated

# **Bore Bearing:**

Not included

# Hub End Outside Diameter And Location:

0.498 inches both ends

# Distance From Outside Flange/rim To Hub End And Location:

 $0.060 \ \text{inches}$  aa end and  $0.050 \ \text{inches}$  bb end

# First Step Length And Location:

 $0.060 \ \text{inches}$  aa end and  $0.050 \ \text{inches}$  bb end

# NSN 3020-01-021-8878

Sprocket Wheel - Page 2 of 2



Second Step Length And Location: 0.110 inches aa end and 0.170 inches bb end Hub End Outside Diameter And Location: 0.498 inches both ends **Special Features:** First end has hexagon shaped counterbore, 0.312 in. Across flats Material: Nylon and fibreglass Material: Nylon and fibreglass Style Designator: Webbed or spoked Surface Treatment: Any acceptable Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T353-c