## NSN 3020-01-022-1763



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-022-1763 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.8021 inches **Teeth Quantity:** 77 **Bore Style:** W/counterbore both ends **Mounting Hole Type And Quantity:** 2 plain transversely through hub between flange and body **Outside Diameter:** 0.822 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.113 inches first end **Face Width:** 0.055 inches **Bore Diameter:** 0.090 inches both ends **Counterbore Depth:** 0.015 inches second end **Counterbore Diameter:** 0.500 inches second end **Hub Style Designator:** 1 groove first end **Hub Diameter:** 0.186 inches first end **Precision Classification:** Quality number 10 or quality number 11 **First Groove Width:** 0.011 inches first end **First Groove Diameter:** 0.165 inches first end **Distance From End To First Groove:** 

0.020 inches first end

**Mounting Hole Diameter:** 

0.031 inches transversely through hub between flange and body

## **NSN 3020-01-022-1763** Spur Gear - Page 2 of 2

Fiig: A27300



| Material:   |
|---|
| Aluminum alloy 2011   |
| Material Specification:                                       |
| Qq-a-225/3, t3 federal specification single material response |
| Style Designator:   |
| Protruding hub  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |