## NSN 3020-01-023-2767

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-023-2767

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.5000 inches
Teeth Quantity:
24
Bore Style:
W/counterbore both ends
Hardness Rating:
40.0 rockwell c
Mounting Hole Type And Quantity:
3 countersunk axially through body, first end
Outside Diameter:
1.625 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.062 inches first end
Face Width:
0.235 inches
Bore Diameter:
0.531 inches both ends
Counterbore Depth:
0.170 inches first end
Counterbore Diameter:
0.625 inches first end
Hub Style Designator:
1 step first end
End Length:
0.047 inches first end
End Diameter:
1.155 inches first end
First Step Length:
0.015 inches first end
First Step Diameter:
1.281 inches first end
Mounting Hole Diameter:

0.147 inches axially through body, first end

## NSN 3020-01-023-2767

Spur Gear - Page 2 of 2

Mil-s-5002 spec.



Material:
Steel uns j03504
Material Specification:
Ams5643 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):