NSN 3020-01-025-1486



Spur Gear - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/3020-01-025-1486
Body Style:
Webbed, offset, with lightening holes
Spline Quantity:
125 both ends
Pitch Diameter:
6.2500 inches
Teeth Quantity:
125
Bore Style:
Involute spline both ends
Spline Pitch Diameter:
3.8000 inches both ends
Hardness Rating:
64.0 rockwell superficial 45-n teeth
Outside Diameter:
6.347 inches
Tooth Form:
Standard
Pressure Angle:
25.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.470 inches both ends
Face Width:
1.060 inches
Bore Diameter:
3.895 inches both ends
Hub Style Designator:
1 step both ends
End Length:
0.375 inches both ends
End Diameter:
4.250 inches both ends
First Step Length:
0.095 inches both ends
First Step Diameter:
4.437 inches both ends

Material:

Steel comp e9310

Material Specification:

Ams6260 assn standard single material response

Surface Treatment:

Phosphate

NSN 3020-01-025-1486

Spur Gear - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Mil-p-16232, type m, class 1 military specification single treatment response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-p-16232 spec.