NSN 3020-01-026-1925

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-026-1925

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.6663 inches **Teeth Quantity:** 160 **Bore Style:** Plain both ends **Backlash Designation:** Grade c Mounting Hole Thread Series Designator: Unc axially through body, first end Mounting Hole Thread Size: 0.138 inches axially through body, first end Mounting Hole Type And Quantity: 3 threaded axially through body, first end **Outside Diameter:** 1.687 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.209 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.375 inches both ends Hub Style Designator: 1 step first end End Length: 0.100 inches first end **Precision Classification:** Quality number 12 End Diameter: 0.745 inches first end First Step Length: 0.110 inches first end **First Step Diameter:** 1.120 inches first end

NSN 3020-01-026-1925

Spur Gear - Page 2 of 2



Bolt Hole Circle Diameter:

0.875 inches axially through body, first end

Material:

Steel comp 303

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.