

View Online at <https://aerobasegroup.com/nsn/3020-01-026-2441>

**Body Style:**

Plain, solid

**Attachment Method:**

Mounting hole

**Pitch Diameter:**

2.3125 inches

**Teeth Quantity:**

74

**Bore Style:**

W/counterbore both ends

**Hardness Rating:**

32.0 rockwell c and 36.0 rockwell c

**Mounting Hole Type And Quantity:**

6 plain axially through body, first end

**Outside Diameter:**

2.375 inches

**Tooth Form:**

Standard

**Pressure Angle:**

20.0000 degrees

**Distance Between Body Face And Protruding Hub End:**

3.032 inches first end

**Body Recess Depth:**

0.124 inches second end

**Face Width:**

0.468 inches

**Bore Diameter:**

0.250 inches both ends

**Counterbore Depth:**

0.344 inches second end

**Counterbore Diameter:**

1.250 inches second end

**Hub Style Designator:**

3 steps first end

**End Length:**

0.625 inches first end

**End Diameter:**

0.499 inches first end

**First Step Length:**

1.875 inches first end

**First Step Diameter:**

0.938 inches first end

**Second Step Length:**

0.781 inches first end

**Second Step Diameter:**

1.001 inches first end

**Third Step Length:**

0.626 inches first end

**Third Step Diameter:**

1.500 inches first end

**Mounting Hole Diameter:**

0.190 inches axially through body, first end

**Special Features:**

3 holes through first step of hub equally spaced 0.186 in.Min, 0.191 in.Max dia. Angular location may vary freely

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-5000, cond c4 military specification single material response

**Style Designator:**

Protruding hub, recessed body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A27300

**Mil-std (military Standard):**

Mil-s-5000 spec.