

View Online at <https://aerobasegroup.com/nsn/3020-01-026-2441>

Body Style:

Plain, solid

Attachment Method:

Mounting hole

Pitch Diameter:

2.3125 inches

Teeth Quantity:

74

Bore Style:

W/counterbore both ends

Hardness Rating:

32.0 rockwell c and 36.0 rockwell c

Mounting Hole Type And Quantity:

6 plain axially through body, first end

Outside Diameter:

2.375 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

3.032 inches first end

Body Recess Depth:

0.124 inches second end

Face Width:

0.468 inches

Bore Diameter:

0.250 inches both ends

Counterbore Depth:

0.344 inches second end

Counterbore Diameter:

1.250 inches second end

Hub Style Designator:

3 steps first end

End Length:

0.625 inches first end

End Diameter:

0.499 inches first end

First Step Length:

1.875 inches first end

First Step Diameter:

0.938 inches first end

Second Step Length:

0.781 inches first end

Second Step Diameter:

1.001 inches first end

Third Step Length:

0.626 inches first end

Third Step Diameter:

1.500 inches first end

Mounting Hole Diameter:

0.190 inches axially through body, first end

Special Features:

3 holes through first step of hub equally spaced 0.186 in.Min, 0.191 in.Max dia. Angular location may vary freely

Material:

Steel comp 4340

Material Specification:

Mil-s-5000, cond c4 military specification single material response

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5000 spec.