NSN 3020-01-026-7431

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-026-7431

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.8751 inches
Teeth Quantity:
96
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
3 threaded transversely through hub, first end
Outside Diameter:
1.534 inches
Tooth Form:
Standard
Flange Diameter:
1.920 inches
Pilot Length:
0.060 inches
Pressure Angle:
20.0000 degrees
Flange Thickness:
0.140 inches
Face Width:
0.386 inches
Bore Diameter:
0.815 inches both ends
Distance Between Outer Body Face And Inner Flange Face:
0.386 inches
Hub Style Designator:
Plain both ends
Hub Diameter:
0.875 inches both ends
Precision Classification:
Quality number 10 or quality number 11

NSN 3020-01-026-7431

Spur Gear - Page 2 of 2



Pilot Diameter:

0.815 inches

Material:

Steel comp 303

Material Specification:

Qq-s-763, cond a federal specification single material response

Surface Treatment:

Passivate

Style Designator:

Flanged end with pilot

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300