NSN 3020-01-026-7431

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-026-7431 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.8751 inches **Teeth Quantity:** 96 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 3 threaded transversely through hub, first end **Outside Diameter:** 1.534 inches **Tooth Form:** Standard Flange Diameter: 1.920 inches Pilot Length: 0.060 inches **Pressure Angle:** 20.0000 degrees Flange Thickness: 0.140 inches **Face Width:** 0.386 inches **Bore Diameter:** 0.815 inches both ends **Distance Between Outer Body Face And Inner Flange Face:** 0.386 inches **Hub Style Designator:** Plain both ends **Hub Diameter:**

0.875 inches both ends **Precision Classification:**

Quality number 10 or quality number 11

NSN 3020-01-026-7431 Spur Gear - Page 2 of 2



Pilot Diameter:
0.815 inches
Material:
Steel comp 303
Material Specification:
Qq-s-763, cond a federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Flanged end with pilot
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300