NSN 3020-01-026-7889

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-026-7889

| Attachment Method: |
|---|
| Mounting hole |
| Teeth Quantity: |
| 160 |
| Bore Style: |
| W/counterbore both ends |
| Pitch Radius: |
| 6.6667 inches |
| Hardness Rating: |
| 89.0 rockwell superficial 15-n teeth and 91.5 rockwell superficial 15-n teeth |
| Mounting Hole Type And Quantity: |
| 9 plain axially through body, first end and 2 countersunk axially through body, first end |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 6.188 inches first end |
| Face Width: |
| 1.125 inches |
| Bore Diameter: |
| 4.125 inches both ends |
| Counterbore Depth: |
| 0.500 inches first end |
| Counterbore Diameter: |
| 5.625 inches first end |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 6.188 inches first end |
| Outside Radius: |
| 6.737 inches |
| Mounting Hole Diameter: |
| 0.281 inches axially through body, first end and 0.312 inches axially through body, first end |
| Bolt Hole Circle Diameter: |
| 6.750 inches axially through body, first end and 6.625 inches axially through body, first end |
| Material: |
| Steel comp e9310 |
| Material Specification: |
| Ams6260 assn standard single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - - |

NSN 3020-01-026-7889

Spur Gear Sector - Page 2 of 2



Demilitarization:

No

Fiig:

A27300