## NSN 3020-01-026-8213

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-026-8213 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 1.1448 inches and 1.1458 inches **Teeth Quantity:** 110 **Mounting Hole Thread Series Designator:** Unc axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 32 axially through body, first end **Mounting Hole Type And Quantity:** 3 threaded axially through body, first end **Outside Diameter:** 1.165 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Bore Diameter:** 0.375 inches both ends **Precision Classification:** Quality number 12 **Bolt Hole Circle Diameter:** 0.750 inches axially through body, first end **Special Features:** A 0.188 in. Diameter hole located on face of gear 0.380 in. Porm 0.010 in. From center of gear, 0.020 in. By 45 degrees chamfer both sides Material: Steel comp 303 **Material Specification:** Qq-s-763, class303 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Style Designator:** Hubless

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 3020-01-026-8213

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.