## NSN 3020-01-028-2805



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-028-2805 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.8334 inches **Teeth Quantity:** 60 **Bore Style:** Plain both ends **Backlash Designation:** Grade e **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches axially through flange **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.861 inches Nominallength: 0.250 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.188 inches first end **Face Width:** 0.062 inches **Bore Diameter:** 0.090 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.312 inches first end Material:

Aluminum alloy 2024

**Material Specification:** 

Qq-a-225/6, t4 federal specification single material response

## NSN 3020-01-028-2805

Spur Gear - Page 2 of 2



Sty	16	u	=5	ıu	 aı	u	ч.	_

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300