NSN 3020-01-028-9335

Spur Gear - Page 1 of 2

Body Style: Plain, solid



View Online at https://aerobasegroup.com/nsn/3020-01-028-9335

Spline Quantity:
14 first end
Attachment Method:
Mounting hole
Pitch Diameter:
59.0 millimeters
Teeth Quantity:
28
Bore Style:
W/counterbore second end
Spline Pitch Diameter:
22.225 millimeters first end
Mounting Hole Type And Quantity:
4 plain axially through body, first end
Outside Diameter:
62.44 millimeters
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
32.0 millimeters first end
Face Width:
10.0 millimeters
Bore Diameter:
25.1 millimeters both ends
Counterbore Depth:
7.5 millimeters second end
Counterbore Diameter:
28.5 millimeters second end
Hub Style Designator:
Plain first end
Hub Diameter:
36.0 millimeters first end
Mounting Hole Diameter:
4.0 millimeters axially through body, first end
Bolt Hole Circle Diameter:
46.0 millimeters axially through body, first end
Special Features:
Plain holes 90 degrees apart

NSN 3020-01-028-9335

Spur Gear - Page 2 of 2

Mil-c-16232 spec.



Material:
Steel
Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-c-16232, type 2 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):