NSN 3020-01-028-9335

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-028-9335

Body Style:

Plain, solid

Spline Quantity:

14 first end

Attachment Method:

Mounting hole

Pitch Diameter:

59.0 millimeters

Teeth Quantity:

28

Bore Style:

W/counterbore second end

Spline Pitch Diameter:

22.225 millimeters first end

Mounting Hole Type And Quantity:

4 plain axially through body, first end

Outside Diameter:

62.44 millimeters

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

32.0 millimeters first end

Face Width:

10.0 millimeters

Bore Diameter:

25.1 millimeters both ends

Counterbore Depth:

7.5 millimeters second end

Counterbore Diameter:

28.5 millimeters second end

Hub Style Designator:

Plain first end

Hub Diameter:

36.0 millimeters first end

Mounting Hole Diameter:

4.0 millimeters axially through body, first end

Bolt Hole Circle Diameter:

46.0 millimeters axially through body, first end

Special Features:

Plain holes 90 degrees apart

NSN 3020-01-028-9335

Spur Gear - Page 2 of 2



Material:

Steel

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-c-16232, type 2 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization: No

110

Fiig:

A27300

Mil-std (military Standard):

Mil-c-16232 spec.