## NSN 3020-01-029-2260

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-029-2260

Body Style:
Plain, solid
Attachment Method:
Clamp
Pitch Diameter:
0.4688 inches
Teeth Quantity:
45
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
0.488 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.292 inches first end
Face Width:
0.094 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.265 inches first end
Precision Classification:
Quality number 10
End Diameter:
0.249 inches first end
First Step Length:
0.027 inches first end
First Step Diameter:
0.310 inches first end
Material:
Steel comp 303
Material Specification:
Qq-s-764, cond a federal specification single material response
Surface Treatment:

Passivate

## NSN 3020-01-029-2260

Spur Gear - Page 2 of 2



Surface	Treatment	Specification:	
Juliace	Heatiment	opecilication.	

Qq-p-35 federal specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300