NSN 3020-01-029-2263

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-029-2263

E	Body Style:
F	Plain, solid
A	Attachment Method:
C	Clamp
F	Pitch Diameter:
1	.0416 inches
T	eeth Quantity:
1	00
E	Bore Style:
F	Plain both ends
C	Outside Diameter:
1	.062 inches
T	ooth Form:
S	Standard
F	Pressure Angle:
2	0.0000 degrees
0	Distance Between Body Face And Protruding Hub End:
0	2.292 inches first end
F	ace Width:
0	0.094 inches
E	Bore Diameter:
0	.187 inches both ends
H	lub Style Designator:
S	Split first end
H	lub Diameter:
0	249 inches first end
C	Clamping Surface Length:
0	2.265 inches first end
١	flaterial:
Α	sluminum alloy 2024
١	Material Specification:
C	Qq-a-225/6, t4 federal specification single material response
S	Surface Treatment:
Α	nodize
S	Surface Treatment Specification:
٨	Ail-a-8625, type 1, class 2 military specification single treatment response
S	Style Designator:
F	Protruding hub
S	Shelf Life:
١	I/a

--

Unit Of Measure:

NSN 3020-01-029-2263

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.