NSN 3020-01-031-8519

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-031-8519 **Attachment Method:** Mounting hole Pitch Diameter: 1.5625 inches **Teeth Quantity:** 75 **Bore Style:** Plain both ends **Mounting Hole Type And Quantity:** 2 plain axially through hub, first end **Outside Diameter:** 1.604 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.139 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** 2 steps first end **End Length:** 0.065 inches first end **End Diameter:** 0.187 inches first end First Step Length: 0.044 inches first end First Step Diameter: 0.437 inches first end Second Step Length: 0.030 inches first end **Second Step Diameter:** 0.750 inches first end **Mounting Hole Diameter:** 0.343 inches axially through hub, first end Material:

Steel comp 303

Surface Treatment:

Passivate

NSN 3020-01-031-8519

Spur Antibacklash Gear - Page 2 of 2



		a 161 41	
Surtace	I reatment	Specification	•

Qq-p-35 federal specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300