## NSN 3020-01-031-9087

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-031-9087

Body Style:
Webbed, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.6008 inches
Teeth Quantity:
60
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches axially through flange
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
0.646 inches
Nominallength:
0.260 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.088 inches first end
Face Width:
0.062 inches
Bore Diameter:
0.125 inches first end
Hub Style Designator:
Pinned first end
Hub Diameter:
0.250 inches first end
Precision Classification:
Quality number 9
End Diameter:
0.219 inches first end
First Groove Width:
0.017 inches first end

## **NSN 3020-01-031-9087** Spur Gear - Page 2 of 2



Distance From End To First Groove:	
0.037 inches first end	
Material:	
Aluminum alloy 6061	
Material Specification:	
Qq-a-225/8, t6 federal specification single material response	
Surface Treatment:	
Anodize	
Surface Treatment Specification:	
Mil-a-8625, type 1, class 1 military specification single treatment response	
Style Designator:	
Protruding hubs	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A27300	
Mil-std (military Standard):	
Mil-a-8625 spec.	