NSN 3020-01-031-9636

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-031-9636

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.9135 inches
Teeth Quantity:
90
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 axially through hub, first end
Mounting Hole Type And Quantity:
1 threaded axially through hub, first end
Outside Diameter:
0.958 inches
Nominallength:
0.306 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Face Width:
0.187 inches
Bore Diameter:
0.090 inches both ends
Precision Classification:
Quality number 9
Quality number 9 First Groove Width:
First Groove Width:
First Groove Width: 0.029 inches first end
First Groove Width: 0.029 inches first end Material:
First Groove Width: 0.029 inches first end Material: Aluminum alloy 6061
First Groove Width: 0.029 inches first end Material: Aluminum alloy 6061 Material Specification:
First Groove Width: 0.029 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response
First Groove Width: 0.029 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response Surface Treatment:
First Groove Width: 0.029 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response Surface Treatment: Anodize
First Groove Width: 0.029 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification:

NSN 3020-01-031-9636

Spur Gear - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.