## NSN 3020-01-033-7754

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-033-7754

Body Style:
Webbed, offset, solid
Attachment Method:
Clamp and mounting hole
Pitch Diameter:
0.3594 inches
Teeth Quantity:
23
Bore Style:
Plain both ends
Mounting Hole Type And Quantity:
1 plain axially through body, first end and 1 plain axially through body, first end
Outside Diameter:
0.390 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.207 inches first end
Face Width:
0.093 inches
Bore Diameter:
0.094 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.1240 inches first end
Clamping Surface Length:
0.1710 inches first end
End Length:
0.1710 inches first end
Precision Classification:
Quality number 9
End Diameter:
0.124 inches first end
First Step Length:
0.067 inches first end
First Step Diameter:

Mounting Hole Diameter:

0.1558 inches first end

0.031 inches axially through body, first end

## NSN 3020-01-033-7754

Spur Gear - Page 2 of 2



Bolt Hole Circle Diameter:
0.115 inches axially through body, first end
Special Features:
Contains 1 drilled hole through one side of hub 0.089 in. @dia
Material:
Steel comp 303
Material Specification:
Aisi 303/sae 30303 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-std-171, finish no. 5.4.1 military standard single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiiq:

Mil-std (military Standard): Mil-std-171 spec.

A27300