## NSN 3020-01-033-7829

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-033-7829

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
4.5000 inches
Teeth Quantity:
216
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
4.540 inches
Nominallength:
0.375 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.437 inches first end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-250/4 t351 federal specification single material response
Surface Treatment:

Anodize

## NSN 3020-01-033-7829

Spur Gear - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Mil-a-8625, type 2, class 1 military specification single treatment response

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.