NSN 3020-01-033-7831

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-033-7831

| Body Style: |
|--|
| Plain, solid |
| Pitch Diameter: |
| 3.0000 inches |
| Teeth Quantity: |
| 144 |
| Bore Style: |
| Plain both ends |
| Outside Diameter: |
| 3.040 inches |
| Nominallength: |
| 0.375 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.250 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.187 inches both ends |
| Hub Style Designator: |
| 1 step first end |
| End Length: |
| 0.092 inches first end |
| End Diameter: |
| 0.265 inches first end |
| First Step Length: |
| 0.158 inches first end |
| First Step Diameter: |
| 0.375 inches first end |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6, t351 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 2, class 1 military specification single treatment response |

Style Designator: Protruding hub

NSN 3020-01-033-7831

Spur Gear - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| N/a | |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.