NSN 3020-01-033-7832

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-033-7832

De du Stude
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.0000 inches
Teeth Quantity:
44
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
0.956 inches
Nominallength:
0.500 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.313 inches first end
Face Width:
0.187 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.500 inches first end
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate

NSN 3020-01-033-7832

Spur Gear - Page 2 of 2



Surface Treatment Specification:

Mil-std-171, finish no. 5.4.1 military standard single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.