## NSN 3020-01-033-8740

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-033-8740 **Body Style:** Webbed, offset, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.9133 inches **Teeth Quantity:** 90 **Bore Style:** W/counterbore both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.958 inches Nominallength: 0.281 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.125 inches first end **Face Width:** 0.062 inches **Bore Diameter:** 

0.090 inches both ends

**Hub Diameter:** 

0.312 inches first end

**Precision Classification:** 

Quality number 10

Material:

Aluminum alloy 6061

**Material Specification:** 

Qq-a-225/8, t6 federal specification single material response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 1, class 1 military specification single treatment response

## NSN 3020-01-033-8740

Spur Gear - Page 2 of 2



Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
<b>Demilitarization:</b> No

Mil-std (military Standard):

Mil-a-8625 spec.