

View Online at <https://aerobasegroup.com/nsn/3020-01-034-8714>

**Outside Diameter:**

3.725 inches

**Overall Length:**

Between 1.088 inches and 1.093 inches

**Bore Diameter:**

Between 1.312 inches and 1.313 inches

**Bore Length:**

Between 1.088 inches and 1.093 inches

**Pitch Diameter:**

3.584 inches

**Face Width:**

Between 0.103 inches and 0.110 inches

**Guide:**

Not included

**Design Form:**

Plain

**Bore Type:**

Straight

**Metallic Hardness Rating And Location:**

25.0 rockwell c hub and 30.0 rockwell c hub

**Counterbore Feature:**

Not included

**Keying Facility:**

Not included

**Lightening Hole:**

Not included

**Protruding Hub Characteristic:**

Plain

**Belt/chain/film Size For Which Designed:**

Roller chain

**Roller Chain Pitch Type For Which Designed:**

Single pitch

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

45

**Asa Standard Chain Number:**

25

**Hardness Rating Test Method:**

Rockwell

**Teeth Hardness Rating:**

Between 25.0 rockwell c and 30.0 rockwell c

**Bore Bearing:**

Not included

**Hub External Keyway:**

Not included

**Tooth Pitch:**

0.250 inches

**Hub End Outside Diameter And Location:**

1.970 inches both ends and 2.030 inches both ends

**Distance From Outside Flange/rim To Hub End And Location:**

0.304 inches both ends and 0.317 inches both ends

**Material:**

Steel, mil-s-5626, comp 4140

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626, comp 4140 military specification single material response

**Surface Treatment:**

Cadmium

**Style Designator:**

Plain

**Surface Treatment:**

Cadmium plated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-c

**Mil-std (military Standard):**

Mil-s-5626 spec.