## NSN 3020-01-035-9392

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-035-9392

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
2.2500 inches
Teeth Quantity:
108
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
2.288 inches
Nominallength:
2.288 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.437 inches first end
Precision Classification:
Quality number 13 or quality number 14
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-268, alloy 2024 federal specification single material response

## NSN 3020-01-035-9392

Spur Gear - Page 2 of 2

Mil-a-8625 spec.



Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Protruding hub
Specification Data:
80205-nas726 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):