## NSN 3020-01-036-2484

Spur Gear - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/3020-01-036-2484

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 1.3531 inches and 1.3541 inches
Teeth Quantity:
65
Bore Style:
Plain both ends
Mounting Hole Type And Quantity:
3 plain axially through body, first end
Outside Diameter:
1.395 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.019 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.625 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
1.200 inches first end
Precision Classification:
Quality number 10 or quality number 11
Mounting Hole Diameter:
0.101 inches axially through body, first end
Bolt Hole Circle Diameter:
1.000 inches axially through body, first end
Material:
Steel comp 303
Material Specification:
Qq-s-763, class303 federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

## NSN 3020-01-036-2484

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Demilitarization:
Jonnai 124110111

Mil-std (military Standard):

Mil-f-14072 spec.