NSN 3020-01-038-1382



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-038-1382 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 4.5000 inches **Teeth Quantity:** 216 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 4.540 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.438 inches first end

Material: Aluminum alloy 2024 **Material Specification:**

Qq-a-225/6, t351 federal specification single material response

Surface Treatment:

Anodize

NSN 3020-01-038-1382

Spur Gear - Page 2 of 2



Surface	Treatment	Specification:
Juliace	HEAUHEIL	opecilication.

Mil-a-8625, type 2, class 1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.