# NSN 3020-01-042-0354

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-042-0354

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.7187 inches **Teeth Quantity:** 69 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unf transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 72 transversely through hub, first end Mounting Hole Thread Size: 0.073 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 threaded transversely through hub, first end **Outside Diameter:** 0.7396 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.046 inches second end Face Width: 0.078 inches **Bore Diameter:** 0.125 inches both ends Hub Style Designator: Plain second end **Hub Diameter:** 0.1660 inches second end End Length: 0.030 inches first end **Precision Classification:** Quality number 10 End Diameter: 0.166 inches first end First Step Length: 0.157 inches first end

# NSN 3020-01-042-0354

Spur Gear - Page 2 of 2



## First Step Diameter:

0.270 inches first end

#### **Special Features:**

Mtg holes 90 degs apart

#### Material:

Steel comp 303

# Material Specification:

Qq-s-764, type 303 federal specification single material response

#### Surface Treatment:

Passivate

#### Style Designator:

Protruding hubs

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

### Fiig:

A27300