

View Online at <https://aerobasegroup.com/nsn/3020-01-044-3808>

Groove Depth:

0.625 inches

Groove Width:

0.688 inches

Outside Diameter:

1.750 inches

Overall Length:

7.438 inches

Drilled Hole Diameter:

0.125 inches

Groove Radius:

0.344 inches

Securing Hole Quantity:

1

Material And Location:

Copper-beryllium alloy, qq-c-530, cond a or h

Face Width:

4.449 inches

Design Form:

Plain

Groove Quantity:

5

Hole Location:

Centered 2.364 in. From end of hub

Securing Method:

Drilled hole and key

Split Hub Feature:

Not included

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

U

Bore Feature:

Not included

Protruding Hub Characteristic:

Plain or stepped

Securing Location:

Aa end

Hub End Outside Diameter And Location:

0.621 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

0.406 inches bb end

First Step Face Largest Diameter And Location:

0.625 inches aa end

First Step Length And Location:

0.438 inches aa end

Second Step Length And Location:

2.145 inches aa end

Hub End Outside Diameter And Location:

0.621 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

2.583 inches aa end

Special Features:

0.745 in. Rim diameter on first end

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a