NSN 3020-01-044-5446



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-044-5446 **Outside Diameter:** Between 6.331 inches and 6.337 inches **Overall Length:** 1.250 inches **Keyway Width:** Between 0.251 inches and 0.253 inches **Thread Size:** 0.250-20 **Bore Diameter:** 1.001 inches **Bore Length:** 1.250 inches **Distance From Center Of Bore To Bottom Of Keyway:** 0.619 inches Pitch Diameter: Between 6.003 inches and 6.005 inches **Securing Hole Quantity:** 2 Face Width: 0.279 inches **Design Form:** Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** 2 holes 0.188 in. From end of hub 90 degrees apart **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Threaded hole **Lightening Hole:** Not included **Protruding Hub Characteristic:** Plain

Securing Location: Aa end

Belt/chain/film Size For Which Designed:

Roller chain

NSN 3020-01-044-5446 Sprocket Wheel - Page 2 of 2



Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
38
Asa Standard Chain Number:
40
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
1.750 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.971 inches aa end
Material:
Steel, qq-s-763, class 302, cond a
Material:
Steel, qq-s-763, class 302, cond a
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c