

View Online at <https://aerobasegroup.com/nsn/3020-01-044-5446>

**Outside Diameter:**

Between 6.331 inches and 6.337 inches

**Overall Length:**

1.250 inches

**Keyway Width:**

Between 0.251 inches and 0.253 inches

**Thread Size:**

0.250-20

**Bore Diameter:**

1.001 inches

**Bore Length:**

1.250 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

0.619 inches

**Pitch Diameter:**

Between 6.003 inches and 6.005 inches

**Securing Hole Quantity:**

2

**Face Width:**

0.279 inches

**Design Form:**

Plain

**Bore Type:**

Straight

**Counterbore Feature:**

Not included

**Hole Location:**

2 holes 0.188 in. From end of hub 90 degrees apart

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole

**Lightening Hole:**

Not included

**Protruding Hub Characteristic:**

Plain

**Securing Location:**

Aa end

**Belt/chain/film Size For Which Designed:**

Roller chain

**Roller Chain Pitch Type For Which Designed:**

Single pitch

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

38

**Asa Standard Chain Number:**

40

**Hardness Rating Test Method:**

Not rated

**Bore Bearing:**

Not included

**Hub External Keyway:**

Not included

**Tooth Pitch:**

0.500 inches

**Hub End Outside Diameter And Location:**

1.750 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

0.971 inches aa end

**Material:**

Steel, qq-s-763, class 302, cond a

**Material:**

Steel, qq-s-763, class 302, cond a

**Quantity:**

1

**Style Designator:**

Plain

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-c