NSN 3020-01-045-4640

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-045-4640 **Attachment Method:** Mounting hole **Teeth Quantity:** 180 **Bore Style:** Plain both ends Pitch Radius: 0.9375 inches **Mounting Hole Thread Series Designator:** Unc transversely through face **Mounting Hole Thread Size:** 0.112 inches transversely through face **Mounting Hole Type And Quantity:** 2 threaded transversely through face **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.345 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.188 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.325 inches first end **Outside Radius:** 0.947 inches Material: Steel comp 416 **Material Specification:** Qq-s-763, class 416, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-std-171, finish no. 5.4.1 military standard single treatment response **Style Designator:** Protruding hub

N/a

Shelf Life:

NSN 3020-01-045-4640

Spur Gear Sector - Page 2 of 2



	In	i+	∩f	RA.	~~	cii	re:
u	,,,	Iι	vı	IVI	ca.	่อน	ıe.

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.