NSN 3020-01-050-5873

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-050-5873

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.5000 inches
Teeth Quantity:
180
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 axially through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded axially through hub, first end
Outside Diameter:
1.516 inches
Nominallength:
0.344 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.219 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.500 inches first end
Special Features:
Both ends of bore 0.010 x 45 degrees chamfer
Material:
Steel comp 303
Material Specification:
Mil-s-7720, comp 303, cond a military specification single material response

NSN 3020-01-050-5873

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-s-7720 spec.



Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-std-171, finish no. 5.4.1 military standard single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300